



SPECIFICATIONS	
Power Supply	115V 60Hz
Motor (fuse size)	2.0 Amps
Motor Type	Universal
Cord	6' Cord
Dimensions (Overall, not including base)	6-1/4" L X 3-1/2" H x 3-1/4" W
Maximum Liquid Temperature	+ 160°F
Minimum liquid temperature	+ 40°F
Pump body material	Bronze
Impeller and lip seal	Nitrile or Polyurethane
Lip seal metal retainer	BL 22
Motor shaft material	416 S.S.
Ports	Dual threaded with 3/4" external hose thread and 3/8" NPT internal suction and discharge
Pump gasket	Paper
Cover	316 S.S.
Shipping weight	5 lbs.

1 FT.	5 FT.	10 FT.	15 FT.	20 FT.	30 FT.	40 FT.	Shutoff
400	390	358	330	295	225	120	48 FT.

All metal construction makes this pump very durable and not subject to damage through heat build-up. This pump is ideal for used oil transfer. Nitrile™ flexible impeller and lip seal help provide up to 400 GPH flow. The bronze pump head has 3/4" OD garden hose threads and 3/8" NPT threads. Pumps will self-prime to 10 ft. and will handle most domestic and commercial utility pumping requirements, as long as the liquid is compatible with the pump materials of construction. Not for use with flammable liquids or liquids not compatible with materials of construction. Flexible Impeller Pump usage should be intermittent and within the temperature range of 40° F and 160° F.