

A superior pump for a rugged environment

LUBEQ's TRUE BLUE PREMIUM Pneumatic Pumps!



We Stand With You.

5:1 and 9:1 Heavy Duty Pneumatic Oil Pumps

Specifications:		
Ratio:	5:1	9:1
Diameter of Air Motor	4.25"	4.25"
Suction Tube Connection	1-1/2"	3/4"
Maximum Air Pressure	120 PSI	120 PSI
Operating Air Pressure	90 PSI	90 PSI
Minimum Air Pressure	60 PSI	60 PSI
Maximum Material Pressure	600 PSI	600 PSI
Air Inlet NPT	1/4" Female	1/4" Female
Material Outlet 5:1 & 9:1 Pumps NPT	3/4" Female	3/8" Female
Max. Sound Level at a Distance of 3 ft	80dB	80dB
Air Consumption, Approx.	14 CFM	14 CFM
Delivery Performance per min at an Operating Pressure of:	450 PSI	810 PSI
Free Flow	10.8 gpm	6.5 gpm
At a Distance of 35 ft	8.0 gpm	5.0 gpm
At a Distance of 100 ft	6.5 gpm	5.0 gpm
At a Distance of 150 ft	2.6 gpm	4.0 gpm
At a Distance of 200 ft	N/A	4.0 gpm

NEW * Pumps now include a 2" bung adapter

Models	Suction Tube Length	5:1 Oil Pumps	9:1 Oil Pumps
Stub Pump	N/A	No 19 500 010	No 19 600 010
16 Gal. Drum	29"	No 19 500 016	No 19 600 016
55 Gal. Drum	38"	No 19 500 055	No 19 600 055
For Tanks with 2" bung adapter	44"	No 19 500 275	No 19 600 275
Recommended: Filter/Regulator/Lubricator	No 20 216	No 20 216	No 20 216



LUBEQ TRUE BLUE Pneumatic Pumps & Equipment